

Page 1 of 1

XP95 I.S. Mounting Base





Product information

The XP95 Intrinsically Safe (I.S.) Mounting Base is designed to accept only I.S. products. This makes sure that standard detectors cannot be inadvertently fitted to an I.S. System.

- Universal XPERT card addressing
- One way fit
- Only accepts I.S. detectors

Addressing

Universal XPERT cards are supplied with all bases. Consult the coding guide in the installation instructions to determine which pips are to be removed from the card to give the correct address.

Technical data

All data is supplied subject to change without notice. Specifications are typical at 22 V, 25°C and 50% RH unless otherwise stated

Standards and approvals	CPR, LPCB, MED, LR, DNV-GL, ABS, BOSEC, RINA, KRS
Dimensions	100 mm diameter x 15 mm height
Weight	62 g
Materials	Housing: White flame-retardant polycarbonate Terminals: Nickel plated stainless steel

Note: The base is part of the detector certification, so does not hold I.S./MED/EMC/CPR certification by itself.

36 Brookside Road, HavantTel: +44 (0)23 9249 2412Email: sales@apollo-fire.comHampshire, P09 1JR, UK.Fax: +44 (0)23 9249 2754Web: www.apollo-fire.co.uk

All information in this document is given in good faith but Apollo Fire Detectors Ltd cannot be held responsible for any omissions or errors. The company reserves the right to change the specifications of products at any time and without prior notice.



LPCB





A **Halma** company © Apollo Fire Detectors Ltd 2021

