

DH-PFM900

Integrated Mount Tester



Features

- 4" IPS screen and QWERTY flip keyboard with 45keys
- Support IP configuration via Onvif protocol
- Support HDCVI/ Analog self-adaptive access
- Support 8x digital zoom
- Support audio and RS485 control
- TDR cable detection and network connection test
- Video screen shot, video recording and playback
- Support POE/ DC12V longer power supply
- Dual LED flashlight

DH-PFM900

Specifications

| | |
|--------------------------------|--|
| Model | DH-PFM900 |
| Physical Port | |
| Network Port | 2*10/100/1000M RJ45 port, support switch mode |
| Function Port | 2*BNC port (Video IN and Video OUT), 1*RS485, 1*Audio In, 1*USB, 1*Reset |
| IPC Test | |
| Protocol | ONVIF 2.4.1, RTSP, RTP |
| Ethernet Test | 10/100/1000M Ethernet link test, loop detect, Ethernet traffic flow monitor, link quality test |
| IP Configuration | static IP/ DHCP client/ DHCP server |
| IPC Test | Discover camera, real time video, camera configuration, PTZ control, audio test, full screen preview and 8x digital zoom, snapshot, record video(recording original data stream) |
| HDCVI & Analog Test | |
| Format | NTSC, PAL |
| Resolution | D1, 720P, 1080P |
| Signal Level | 1Vpp |
| Camera Test | Real time video, PTZ control, audio test, full screen preview and 8x digital zoom, snapshot, record video(H.264) |
| HDCVI OSD | Camera configuration |
| PTZ Control | |
| Protocol | More than 30 protocols including Dahua, Pelco-D/P, Samsung, Panasonic, Lilin, Yaan etc. |
| Baud Rate | 150, 300, 600, 1200, 2400, 4800, 9600, 19200bps |
| Detection | |
| TDR detection | 0~150m net cable detection, resolution 2m |
| POE test | PD test |
| | PSE test |
| Network Analyze | Sniff, list subnet, ping |
| Analog Video Generator | Generate PAL/ NTSC video signal of various test pattern |
| Record Playback | Support local playback |
| System Specification | |
| Screen | 4.0 inch TFT 800*RGB*480(WVGA) resolution, 16.7M color, backlight brightness adjustable |
| Operation Method | Power key, 12 control keys, QWERTY flip keyboard with 45 keys |
| Auto Power Off | Disable/ 5~60 minutes |
| Keyboard Tone | Enable/ Disable |
| Upgrade | Support online upgrade |
| Power | |
| Power Input | POE port by POE midspan |

DH-PFM900

| | |
|---------------------|---|
| POE Midspan | Input AC100~230V 50~60Hz, output 48V/15w |
| Battery | Dedicate battery, user replaceable, 7.4V lithium-ion polymer battery, capacity 22.2Wh |
| Power Output | POE (802.3af, 802.3at) |
| | DC12V 2A |
| Time | Charging time 3~4 hours, working time 10 hours |
| Other | |
| Internal Storage | 8GB flash |
| LED Light | 2*35lm LED light |
| Working Temperature | -10°C ~ +55°C |
| Working Humidity | 30%~90% |
| Dimensions | 190x113x37mm |
| Weight | 0.5Kg |

Application



Dahua Technology Co., Ltd.

1199 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuasecurity.com

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.