



PVC ALARM CABLE TINNED COPPER - SHIELDED

Cables for permanent instalaltion suitable for alarm and intruder systems.
Compliant with Construction Product Regulation CPR



TECNICAL FEATURES

CONDUCTORS

Flexible Tinned copper

INSULATION

PVC

ASSEMBLY

conductors stranded in layers

SCREEN


Alluminium/polyester tape
Drain wire flexible tinned copper

JACKET

WHITE PVC

PACKAGING AVAILABLE

Spool 100 mt.



MARKING

meter

COLOUR CONDUCTOR

RED,BLUE,YELLOW,BLACK ,WHITE,GREEN,ORANGE, BROWN,
GREY, PINK,VIOLET,TURQUASE

PRODUCTS:

Code	Nominal Section	Outer dia. +/- 0,2mm	Copper formation	Conductor resistance Ohm/Km	Jacket colour
4SALTC15	PVC ALARM CABLE SHIELDED TC 4X0.22	3,30	7x0.15	140	WHITE
6SALTC15	PVC ALARM CABLE SHIELDED TC 6X0.22	3,90	7x0.15	140	WHITE
8SALTC15	PVC ALARM CABLE SHIELDED TC 8X0.22	4,80	7x0.15	140	WHITE
12SALTC15	PVC ALARM CABLE SHIELDED TC 12X0.22	5,30	7x0.15	140	WHITE

ELECTRICAL FEATURES

TEST VOLTAGE

1000 V

INSULATION RESISTANCE

> 200 MΩ/Km

TEMPERATURE RANGE

-10° / +70°

BENDING RADIUS

10 X Ø

STANDARDS

Insulation and sheath	CEI EN 50363
Flame retardant	IEC 60332-1-2
coexistence with cables CAT. 1	UNEL 36762
European directive	Rohs 2011/65/EU

CPR REACTION CLASS

Harmonized standard EN 50575:2014 + A1:2016

Reaction to fire **Eca**

Hazardous substance Nothing

Marking: **CE**



KTS S.r.l. - Via Madonna delle Grazie, 53 - 80018 Mugnano di Napoli - Napoli - Italy
Tel: +39 081 5713050 commerciale@ktsables.com

www.ktsables.com